MATERIAL SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

564700

Reviewed on: 03/11/2010

Printing date: 03/11/2010

01 Identification of the substance/preparation and of the company/undertaking

- · Product details
- Trade name:

ZKZ-08000 colour pigment orange Application of the substance / the preparation

Cosmetic ingredient

Manufacturer/Supplier:

Gildewerk B.V.

Jan van Geunsweg 10A, 2031 BD Haarlem, The Netherlands

Tel. +31 - (0)23 - 532 22 55

Fax +31 - (0)23 - 534 09 65

E-mail holland@gildewerk.com

www.gildewerk.com

02 Hazards identification

Hazard description:

Not applicable.

Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Prevent formation of dust.

GHS label elements

Void

03 Composition/information on ingredients

· Dangerous components:

Description Index R-phrases CAS NO. Non applicable / Not applicable

%

04 First aid measures

· General information:

No special measures required.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

If symptoms persist consult doctor.

05 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment:

Wear fully protective suit.

GB

MATERIAL SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

564700

Reviewed on: 03/11/2010

Printing date: 03/11/2010

PRODUCT: ZKZ-08000 colour pigment orange

(continued of page 1)

06 Accidental release measures

· Person-related safety precautions:

Wear protective clothing.

· Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Measures for cleaning/collecting:

Dispose contaminated material as waste according to item 13.

Pick up mechanically.

07 Handling and storage

· Handling:

· Information for safe handling:

Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of dust.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

· Information about fire - and explosion protection:

Protect against electrostatic charges.

Storage:

Durée de vie / Shelf life :

10 years

T°.<25℃

Tout conditionnement ouvert doit être testé chaque année / After opening, product must be rechecked every year

· Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

· Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Protect from exposure to the light.

Caution when reopening receptacles with broken seal.

Open receptacle only under localized extractor facilities.

Store receptacle in a well ventilated area.

Protect from humidity and water.

08 Exposure controls/personal protection

· Ingredients with limit values that require monitoring at the workplace:

France: Poussières totales: 10 mg/m3/8h - Poussières alvéolaires: 5 mg/m3/8h - French maximum permitted exposure levels: 10 mg/m3/8h: Total dust by inhalation - 5 mg/m3/8h: alveolary dust.

Additional information:

The lists valid during the making were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

- Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.
- · Recommended filter device for short term use:

Filter P3

- · Protection of hands: Protective gloves
- · Material of gloves

Nitrile rubber, NBR

- · Eye protection: Safety glasses
- · Body protection: Use protective suit.

GB

MATERIAL SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

564700

Reviewed on: 03/11/2010

Printing date: 03/11/2010

PRODUCT: ZKZ-08000 colour pigment orange

(continued of page 2)

09 Physical and chemical properties

General Information

Form: Powder Colour: Red

Solubility in / Miscibility with

water:Insoluble.vegetable oils:Insoluble.paraffin oil:Insoluble.

10 Stability and reactivity

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Dangerous decomposition products:

No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values relevant for classification:

Oral, LD50: > 2000 mg/kg (rat) *

- Primary irritant effect:
- · on the skin: *

No irritant effect.

· on the eye: *

No irritating effect.

· Additional toxicological information:

RTECS n°QL3436000 / FDA - EEC: positive lists

12 Ecological information

· Behaviour in sewage processing plants:

The product can be mechanically separated.

· General notes:

At present there are no ecotoxicological assessments.

13 Disposal considerations

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

14 Transport information

Land transport ADR/RID (cross-border)

ADR/RID class:

Maritime transport IMDG:

IMDG Class:

· Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class:

GB

Page: 4/4

MATERIAL SAFETY DATA SHEET according to 1907/2006/EC, Article 31

564700 Reviewed on: 03/11/2010

Printing date: 03/11/2010

PRODUCT: ZKZ-08000 colour pigment orange

(continued of page 3)

15 Regulatory information

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VCI: Verband der chemischen Industrie, Deutschland (German chemical industry association)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Gildewerk B.V.

Jan van Geunsweg 10A, 2031 BD Haarlem, The Netherlands

Tel. +3I - (0)23 - 532 22 55 Fax +3I - (0)23 - 534 09 65 E-mail holland@gildewerk.com www.gildewerk.com

TECHNICAL BULLETIN

ZKZ-08000 colour pigment orange

<u>DEFINITION</u>

Pigment monoazoïque Monoazoïc pigment

LEGISLATION LEGISLATION

COLOUR INDEX 12085
INCI CI 12085
C.A.S. NUMBER 2814 - 77 - 9

EINECS 220 - 562 - 2 F.D.A. **D&C red 36** (3 %

cosmétiques - 3 % max

Allowed in all cosmetic products - 3 % max

C.E.E. ALIMENTATION

(95/45/EC incl. amendments)

JAPAN

Red N°228

FORMULE CHIMIQUE CHEMICAL STRUCTURE

$$O_2N$$
 \longrightarrow $N=N$

PROPRIETES PHYSICO CHIMIQUES

PHYSICAL AND CHEMICAL PROPERTIES

31.08.05

Aspect poudre/powder Aspect
Teneur en colorant pur 95 % Mini Pure dye content
Solubilité eau insoluble Water solubility
Stabilité lumière moyenne/moderate Fastness to light

SPECIFICATIONS SPECIFICATIONS

Matières volatiles (135°C) 1,5% max Volatile matter (135°C) Produits insolubles dans 1,5% max Matter insoluble in toluene toluène

Intermédiaires, colorants passe le test/ Intermediates, subsidiary

accessoires passes test colors

METAUX LOURDS p.p.m. HEAVY METALS p.p.m.

PLOMB 0-10 LEAD ARSENIC 0-3 ARSENIC MERCURE 0-1 MERCURY