HV Floating Universeel:

COMPONENTS	COMPONENTS					
INCI-Name	CAS-nummer	Concentration %				
Aqua		90,52				
Sodium Laureth Sulfate, Glycine	68585-34-2 56-40-6	7,00 0,04				
Acrylates Copolymer	-	2,040000				
Sodium Hydroxide	1310-73-2	0,243200				
Disodium EDTA	139-33-3	0,050000				
Benzophenone-4	4065-45-6	0,050000				
Benzyl Alcohol, Methylchloroisothiazolinone, Methylisothiazolinone, Propylene Glycol, Magnesium Nitrate, Magnesium Chloride	100-51-6 26172-55-4 2682-20-4 57-55-6 10377-60-3 7786-30-3	0,014300 0,000990 0,000330 0,034100 0,008800 0,001100				

INCI: HV Floating

AQUA
SODIUM LAURETH SULFATE
ACRYLATES COPOLYMER
SODIUM HYDROXIDE
DISODIUM EDTA
BENZOPHENONE-4
BENZYL ALCOHOL
PROPYLENE GLYCOL
METHYLCHLOROISOTHIAZOLINONE
METHYLISOTHIAZOLINONE
MAGNESIUM NITRATE
MAGNESIUM CHLORIDE
GLYCINE



This SDS is an English translation of Regulation (EU) n^{o} 2015/830, without any country-specific legislation

www.gildewerk.com

ZUH-02000 - HV Floating Universeel



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier: ZUH-02000 HV Floating Universeel
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Shampoo (human use). For industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Gildewerk B.V. A Hofmanweg 41 2031BH Haarlem +31 (0)23 532 22 55 support@gildewerk.com www.gildewerk.com

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No. 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319 Met. Corr. 1: Corrosive to metals, Category 1, H290

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation Met. Corr. 1: H290 - May be corrosive to metals

Precautionary statements:

P234: Keep only in original packaging

P264: Wash thoroughly after handling

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313: If eye irritation persists: Get medical advice/attention

P390: Absorb spillage to prevent material damage

P406: Store in a corrosion resistant/container with a resistant inner liner

Supplementary information:

 ${\tt EUH208: Contains METHYLCHLOROISOTHIAZOLINONE / METHYLISOTHIAZOLINONE. May produce an allergic reaction}$

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:



This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

www.gildewerk.com

ZUH-02000 - HV Floating Universeel



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification		Concentration
CAS: 68891-38-3		Alcohols, C12-14(even numbers	ed), ethoxylated < 2.5 EO, sulfates, sodium salts[]'[]	Self-classified	
EC: Index: REACH:	500-234-8 Non-applicable 01-2119488639-16-XXXX	Regulation 1272/2008	Aquatic Chronic 3: H412: Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger		5 - <10 %
CAS: 1310-73-2 sodium		sodium hydroxide0'0		Self-classified	
EC: 215-185-5 Index: 011-002-00-6 REACH: 01-2119457892-27-XXXX	011-002-00-6	Regulation 1272/2008	Eye Dam. 1: H318; Met. Corr. 1: H290; Skin Corr. 1A: H314 - Danger		<1%
CAS:	55965-84-9	reaction mass of 5-chloro-2-n	nethyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)[] ⁻ []	ATP ATPI3	
EC: Index: REACH:	Non-applicable 613-167-00-5 Non-applicable	Regulation 1272/2008	Acute Tox. 2: H3(0+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger		∢%

D'O Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

	Identification		M-factor		
reaction mass of 5-chloro-2-meth	/I-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Acute	100		
CAS: 55965-84-9	EC: Non-applicable	Chronic	100		

Identification	Specific concentration limit
Alcohols, Cl2-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts CAS: 68891-38-3 EC: 500-234-8	% (w/w) >=10: Eye Dam. I - H318 5<= % (w/w) <10: Eye Irrit. 2 - H319
sodium hydroxide CAS: 1310-73-2 EC: 215-185-5	% (w/w) >=0.1: Met. Carr. 1 - H290 % (w/w) >=5: Skin Carr. 1A - H314 2<= % (w/w) <5: Skin Carr. 1B - H314 0.5<= % (w/w) <2: Skin Irrit. 2 - H315 % (w/w) >=0.5: Eye Irrit. 2 - H319
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	96 (w/w) >= 0.6: Skin Corr. IC - H314 0.06<= % (w/w) <0.6: Skin Irrit. 2 - H315 96 (w/w) >= 0.6: Eye Dam. 1 - H318 0.06<= % (w/w) <0.6: Eye Irrit. 2 - H319 96 (w/w) >= 0.0015: Skin Sens. 1A - H317

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact

In case the skin is affected (stinging, redness, rashes, blisters,...), seek medical help with this Safety Data Form.

By eye contact

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES



This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

www.gildewerk.com

ZUH-02000 - HV Floating Universeel



SECTION 5: FIREFIGHTING MEASURES (continued)

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

 $\begin{aligned} & \text{Minimum Temp.:} & & 5 \, ^{\circ}\text{C} \\ & \text{Maximum Temp.:} & & & 30 \, ^{\circ}\text{C} \\ & \text{Maximum time:} & & 6 \, \text{Months} \end{aligned}$

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE
Date of compilation: 20/10/2020 Version: 1

Page 3/10



www.gildewerk.com

Safety data sheet

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

ZUH-02000 - HV Floating Universeel



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short e	xposure	Long ex	kposure .
Identification		Systemic	Local	Systemic	Local
Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 6889I-38-3	Dermal	Non-applicable	Non-applicable	2750 mg/kg	Non-applicable
EC: 500-234-8	Inhalation	Non-applicable	Non-applicable	175 mg/m³	Non-applicable
sodium hydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1310-73-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-185-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	1 mg/m³

DNEL (General population):

		Short e	xposure	Long e:	cposure .
Identification		Systemic	Local	Systemic	Local
Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
CAS: 68891-38-3	Dermal	Non-applicable	Non-applicable	1650 mg/kg	Non-applicable
EC: 500-234-8	Inhalation	Non-applicable	Non-applicable	52 mg/m³	Non-applicable
sodium hydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1310-73-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-185-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	1 mg/m³

PNEC:

Identification				
Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts	PTS	10000 mg/L	Fresh water	0,24 mg/L
CAS: 68891-38-3	Sail	7,5 mg/kg	Marine water	0,024 mg/L
EC: 500-234-8	Intermittent	0,071 mg/L	Sediment (Fresh water)	0,917 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,092 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection....) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Non-applicable

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2001 En ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clathing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.



This SDS is an English translation of Regulation (EU) n^2 2015/830, without any country-specific legislation



www.gildewerk.com

ZUH-02000 - HV Floating Universeel

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-I ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.D.C. (Supply):

V.D.C. density at 20 °C:

Average carbon number:

Average molecular weight:

Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 ℃:

Appearance:

Colour:

Not available

Odour:

Not available

Odour:

Non-applicable*

Volatility:

Boiling point at atmospheric pressure: 100 $^{\circ}$ C Vapour pressure at 20 $^{\circ}$ C: 2350 Pa

Vapour pressure at 50 $^{\circ}$ C: 12379,48 Pa (12,38 kPa) Evaporation rate at 20 $^{\circ}$ C: Non-applicable *

Product description:

Density at 20 °C: 1036.8 kg/m³
Relative density at 20 °C: 1.037

Dynamic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 40 °C: Non-applicable *
Concentration: Non-applicable *
pH: Non-applicable *

Vapour density at 20 °C:

Partition coefficient n-octanol/water 20 °C:

Solubility in water at 20 °C:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 20/10/2020 Version: 1



Safety data sheet This SOS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

www.gildewerk.com

ZUH-02000 - HV Floating Universeel



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 $^{\circ}$ C)
Flammability (solid, gas): Non-applicable *
Autoignition temperature: 421 $^{\circ}$ C
Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Explosive:

Lower explosive limit:

Upper explosive limit:

Non-applicable *
Non-applicable *

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Not applicable

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):



This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

www.gildewerk.com

ZUH-02000 - HV Floating Universeel



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3
 - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: Non-applicable
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3
 - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acı	Genus	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LOSO oral	100 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	300 mg/kg	Rat
EC: Non-applicable	LC50 inhalation	Non-applicable	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity	
Oral	>2000 mg/kg (Calculation method)	Non-applicable	
Dermal	>2000 mg/kg (Calculation method)	Non-applicable	
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:



This SDS is an English translation of Regulation (EU) n^{o} 2015/830, without any country-specific legislation

ZUH-02000 - HV Floating Universeel



SECTION 12: ECOLOGICAL INFORMATION (continued)

www.gildewerk.com

Identification	Acute toxicity		Species	Genus
Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts	LC50	7.1 mg/L (96 h)	Danio rerio	Fish
CAS: 6889I-38-3	EC50	7.4 mg/L (48 h)	Daphnia magna	Crustacean
EC: 500-234-8	EC50	27 mg/L (72 h)	Scenedesmus subspicatus	Algae
sodium hydroxide	LC50	189 mg/L (48 h)	Leuciscus idus	Fish
CAS: 1310-73-2	EC50	33 mg/L	Crangon crangon	Crustacean
EC: 215-185-5	EC50	Non-applicable		
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 55965-84-9	EC50	0.1 - 1 mg/L		Crustacean
EC: Non-applicable	EC50	0.1 - 1 mg/L		Algae

12.2 Persistence and degradability:

Identification	Degr	adability	Biodegradability	
Alcohols, C12-14(even numbered), ethoxylated < 2.5 EO, sulfates, sodium salts	B0D5	Non-applicable	Concentration	10.5 mg/L
CAS: 68891-38-3	COD	Non-applicable	Period	28 days
EC: 500-234-8	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
It is not possible to assign a specific code, as it depends on the intended use by the user		Non dangerous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 DI (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation



www.gildewerk.com

ZUH-02000 - HV Floating Universeel

SECTION 14: TRANSPORT INFORMATION (continued)



UN1760 14.1 UN number: 14.2 UN proper shipping name: CORROSIVE LIQUID, N.O.S. (sodium hydroxide)

14.3 Transport hazard class(es): 8 Lahels: 14.4 Packing group: Ш

14.5 Environmental hazards: Nπ 14.6 Special precautions for user

> 274 Special regulations: Tunnel restriction code: Ε

Physico-Chemical properties: see section 9 Limited quantities: 51

14.7 Transport in bulk according to Annex II of Non-applicable

Marpol and the IBC Code:

Transport of dangerous goods by sea:

14.3

14.4

14.5

14.7

14.7

With regard to IMDG 39-18:



UN1760 141 IIN number-

CORROSIVE LIQUID, N.O.S. (sodium hydroxide) 14.2 UN proper shipping name:

Transport hazard class(es): Labels: Ш Packing group: Environmental hazards:

14.6 Special precautions for user

Special regulations: 274, 223 EmS Codes: F-A. S-B see section 9 Physico-Chemical properties: Limited quantities: 5 L Segregation group: Non-applicable Transport in bulk according to Annex II of Non-applicable

Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAD 2020:



IIN1760 14.1 IIN number-

CORROSIVE LIQUID, N.O.S. (sodium hydroxide) 14.2 UN proper shipping name:

14.3 Transport hazard class(es): Labels: Packing group: 14.4 14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9 Transport in bulk according to Annex II of Non-applicable

Marpol and the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2methyl-2H-isothiazol-3-one (3:1).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

- CONTINUED ON NEXT PAGE -Page 9/10 Date of compilation: 20/10/2020 Version: 1



www.gildewerk.com

Safety data sheet

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

ZUH-02000 - HV Floating Universeel



SECTION 15: REGULATORY INFORMATION (continued)

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-annlicable

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation H290: May be corrosive to metals

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled

Acute Tox. 3: H3DI - Toxic if swallowed

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage

Met. Corr. 1: H290 - May be corrosive to metals

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage

Skin Corr. IC: H314 - Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1A: H317 - May cause an allergic skin reaction

Classification procedure:

Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 20/10/2020 Version: 1

Page 10/10